ANGSA SAMPLE SELECTION AND THE VARIOUS CURATION CHALLENGES IN PROCESSING AND ALLOCATING THE SAMPLES. Ryan A. Zeigler¹, Juliane Gross^{1,2}, Scott Eckley^{3,4}, Andrea Mosie³, Charis Krysher³, Jeremy Kent³, Cecilia L. Amick, Ernest K. Lewis, and Francis M. McCubbin¹ and The ANGSA Science Team⁵, ¹NASA Johnson Space Center, Houston, TX 77058, USA. ²Rutgers State University of New Jersey, Department of Earth & Planetary Sciences, Piscataway, NJ 08854, USA, ³ Jacobs Technology, Johnson Space Center, Houston, TX ⁴Jackson School of Geosciences, University of Texas at Austin, Austin TX, ⁵ANGSA Science Team list at https://www.lpi.usra.edu/ANGSA/teams/.

Introduction and Overview: From 1969-1972, the Apollo missions collected 2196 individual samples of rock and regolith from the Moon (382 kg total mass). Although all Apollo samples can be included in the rock and regolith categories, across the six missions a huge variety of rock lithologies were collected, e.g., rake, float samples, and boulder subsamples; a similarly wide variety of regolith samples were collected, e.g., skim and trench soils, soils from shaded areas, deep drill cores and drive tubes, as well as some that were sealed under vacuum or frozen after they were returned to Earth. Over the past 50 years, there have been over 3300 Apollo sample requests, utilizing >10,000 subsamples from 2190 of the original 2196 samples. These myriad studies have shaped out understanding not only of the Earth-Moon system but also the terrestrial planets, airless bodies like asteroids, the formation locations of the gas giants, and have even acted as a record of the radiation history of our solar system as it has revolved around the galaxy for the past 4.6 Ga.

Despite all of these studies and all of this knowledge gained, there is still more to be learned from the Apollo samples. To this end, NASA solicited proposals to study unopened or specially curated Apollo samples as part of the Apollo Next Generation Sample Analysis (ANGSA) Program. Prior to the ANGSA program being initiated there were six Apollo samples that have never been opened: (1) unsealed regolith drive tubes 73002 and 70012; (2) sealed drive tubes 69001 and 73001; (3) sealed bulk soil sample 15014; and (4) frozen basalt sample 71036. Additionally, there were portions of other Apollo 17 regolith samples that have been stored frozen since shortly after they were returned, as well as a suite of Apollo 15 sealed regolith samples (from samples 15012/15013) that were opened, processed, and continuously stored since then in a He-purged environment (most Apollo samples are stored in N-purged environments). These samples were purposefully saved to be opened or studied at a future date where instrumentation had improved enough to give scientists the chance to maximize the scientific return on the samples.

NASA selected nine consortia of scientists to study a subset of the previously unexamined samples. The samples selected were: unsealed drive tube 73002, sealed drive tube 73001 (part of a double drive tube pair with 73002), and frozen basalt sample 71036. These

samples were selected for a variety of reasons, including: (1) The 73001/2 drive tubes are spatially associated with landslides and a fault at the Apollo 17 site; (2) from a practicality standpoint, having an unsealed core that could be studied immediately (without having to extract the gas) would allow for the program to start more quickly; and (3) the sealed and cold samples had obvious ties to the upcoming Artemis missions.

Curation Methodology: Each of the samples included in the ANGSA program had their own unique challenges during the curation process.

Sample 73002 was the first drive tube sample to be opened in over 25 years. This meant that all of the equipment that was needed for the extrusion and dissection process had to located, cleaned, assembled, and tested (including procurement of replacement parts where needed). Similarly, the procedures for sample dissection had to be reviewed and modernized, which included building a full-sized cabinet mock-up and extensive testing with analog samples. During the actual dissection process, several non-standard dissection procedures were also implemented such as time-sensitive sampling and mm-scale subsampling in the top two intervals. After dissections required that the entire core vacuum impregnation and curing devices had to be rebuilt.

With sample 73001, the most obvious hurdles were related to how to get the gas out of the outer vacuum container (OVC) and Core Sample Vacuum Container (CSVC) prior to opening the samples. This involved building two bespoke pieces of hardware, a gas-extraction manifold built at Washington University in St. Louis [1] and a piercing tool built at ESA [2], as well as the actual assembly, integration, and operation of this equipment within the materials constrained environment of the JSC clean rooms.

The ability to process frozen samples at -20° C was not a capability that existed at JSC prior to ANGSA, and an existing Apollo glovebox had to be retrofit to work at those temperatures. Significant facility modifications to the walk-in freezer in the JSC Experimental Impact Lab to make it material and environmentally compliant with processing of Apollo samples was also required [3]. Similarly, the procedures for how to process the samples under these extreme conditions had to be developed and implemented [4].

This was the first time that X-ray Computed Tomography (XCT) was used as part of the curation process for drive tube dissection. Whole-core scans were made of both 73002 and 73001 prior to extrusion and dissection at the University of Texas High-Resolution X-ray Computed Tomography (UTCT) Facility for high-resolution scanning. Both of these scans had unique challenges that were overcome to give excellent data sets that proved invaluable to both the curation and mission science teams [5]. Over 350 particles in the 4-10 mm and >10 mm size particle size fractions were separated during dissection, individually bagged in Teflon (3 bags), and scanned by XCT at NASA JSC [6]. These scans allowed for the identification of different lithologies within the particles, which greatly helped with the request and allocation process [7].

Finally, a Keyance petrographic microscope was used to map all eight of the 73002 continuous core thin sections (two sets of four sections) at a resolution of a few microns per pixel. These were provided to the ANGSA science teams to serve as base maps for the more detailed electron- and ion-beam work that would come later.

Summary: The ANGSA program was designed to help us prepare for the upcoming Artemis missions, while at the same time getting important new scientific results from the Apollo samples. Each of the samples included in the ANGSA program had their own unique challenges related to the curation process, and the work on this program has greatly enhanced our readiness for the next batch(es) of lunar samples to come back.

References: [1] Parai R. et al. (2021) *LPSC 52*, #2665. [2] McDonald F. et al. (2022) *EPSC2022*, #1117. [3] Amick C. et al. (2020) *LPSC 51*, #1632. [4] Kent J. J. et al. (2022) *Metsoc 85*, #6497. [5] Ketcham R. A. et al. (2022), this volume. [6] Zeigler R. A. et al. (2021) *LPSC 52*, #2632. [7] Shearer C. K. et al. (2022), this volume.