

**Technical Study upon the Concept for Energy Production at Lunar Poles using a Meshed Network of Thermoelectric Generators.** Neelesh Ranjan Saxena, Department of Aeronautics and Astronautics, Technische Universität Berlin (Marchstraße 12, 10587 Berlin, Germany/ info@mse.tu-berlin.de)

**Introduction:** Ever since NASA's Lunar Reconnaissance Orbiter (LRO) has started data-keeping from its lunar orbit in high accuracy, it has continued to help narrow down the possible locations feasible for a human settlement for the future. These locations are shortlisted usually either based upon the availability of sunlight present throughout the year as in case of Peaks of Eternal Light (PELs)<sup>[1]</sup> or they employ the geographical features of the local terrain for the purpose of radiation protection as in case of skylights and lava tubes/lava caves<sup>[2]</sup>.

What remains common in all such sites is that they are all primarily powered by solar energy, based upon which an electricity-driven manned base shall function. So the permanent visibility of the Sun or at least an unhindered access to solar power remains a crucial factor when it comes to operating these bases for long durations. However, it is equally important to see that for redundancy purposes, sunlight should not be relied upon as the sole basis of energy especially during the times when, say, a situation involving a shortage/outage of power comes up such as eclipses.

Along the same line of thought, this paper attempts to empirically evaluate the feasibility of setting up and using a large number of interconnected Thermoelectric Generator (TEG) mesh as an alternative to making use of large thermal gradients found in-situ near the polar regions of the Moon. In addition to that, the idea of drawing sufficient amount of usable energy is also explored, from the vast temperature difference that exists locally on the sunlit side of the Moon particularly near places like poles, mountains, skylights and craters near the permanently shadowed regions (especially the likes of Shackleton and Malapert among others that exist around the Lunar South Pole). Thereby, a fresh perspective towards a non-conventional method of energy generation is introduced by bringing in a supplementary way of siphoning usable power without putting additional burden over the existing state of the manufacturing and installation abilities of our time.

Sufficient efforts are further made to present a fair comparison of such an alternative by evaluating its efficiency, power budget, setup costs and operational challenges with other conventional methods. The observations and results of the study towards the end

present promising outputs if the proposed setup of TEGs is employed over the above mentioned locations.

**Acknowledgments:** A humble gratitude in the development of this technical paper needs to be shown towards NASA's Planetary Data System for providing free and open access to its highly useful tools such as PDS Image Atlas at the Cartography and Imaging Sciences Node and Map-A-Planet 2 (MAP2) at the Cartography and Imaging Sciences Node, because of which a lot of research that went into the making of this paper was made possible.

Additionally, a couple of other useful tools were also involved in the completion of this work, especially the likes of LROC Quickmap, NASA Moon Trek and Permanently Shadowed Regions Atlas, all of whose help is humbly acknowledged here.

**References:** [1] Speyerer, Emerson J., and Robinson, Mark S. (2013). "Persistently illuminated regions at the lunar poles: Ideal sites for future exploration", *Icarus*, **222**, No. 1, January, pp. 122–136. [2] Handwerk, Brian (October 26, 2009), *First Moon 'Skylight' Found -- Could House Lunar Base?*, National Geographic, archived from the original on 2011-10-10, retrieved 2011-01-27